# Eaton 5SC1500IRBS

# Catalog Number: 5SC1500IRBS

Eaton 5SC UPS, 1500 VA, 1050 W, Input: C14, Outputs: (8) C13, Rack, 2U, with BS input cord

# General specifications

**Product Name** 

Eaton 5SC UPS

Model Code

**Product Height** 

**Product Weight** 

86.2 mm

17.78 kg

Eaton 5SC 1500i Rack2U w/ BS Cord

10A

Catalog Number

5SC1500IRBS

EAN

3553340620348

Product Length/Depth

440 mm

**Product Width** 

405 mm

Compliances

CE Marked

TUV



# Certifications

IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC

cTUVus

UL 1778



# **Battery**

Battery type

Lead-acid maintenance-free (replaceable)

Runtime graph

View runtime graph

Battery replacement

User replaceable

Battery quantity

3

Battery management

ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection

Battery rating

12 V / 9 Ah

Extended battery capability

No

# Electrical output

Receptacle

(8) C13

Voltage

230V

Wattage

1050 W

Output power factor

0.7

Output voltage range

230 V (+6%/-10%)

Output waveform

Sine wave

Output nominal voltage

230V default (220/230/240V)

Feed type

1

**Topology** 

Line-interactive

VA rating

1500 VA

# Electrical input

Input connection

C14

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50-60 Hz

Input voltage range

184-276 V

Input frequency range

45-55 Hz (50 Hz system), 55-65 Hz (60 Hz system)

# Communications

Includes network card

No

Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote On/Off and Remote Power Off

Dry contacts (2 outputs, optocoupler, RJ)

Ethernet interface

No

User interface

LCD Display

Potential free switch contact

Yes

# **Expansion slots**

One slot for optional communication card

# Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power

Protector

# Type of interface

Other

# **Environmental**

#### Altitude

3000 m

#### Noise level

<40 dB at 1 meter

# Temperature range

0-90% non-condensing

#### Relative humidity

0-90% non-condensing

# Additional specifications

# Construction type

482.6 mm (19 inch) device

#### **Enclosure**

Black

# Package contents

Rack-mounting kit

Cable locking system

USB cable

Serial cable

(2) IEC-IEC cables

Quickstart guide

Safety instructions

BS input cord

# Phase (output)

1

# Auto shutdown function

Yes

Color

Black

#### Efficiency

97

# Rack mounting kit

Yes

# Phase (input)

1

# Resources

#### **Brochures**

Eaton UPS Services Quick Guide 2021

Eaton UPS and battery services

Eaton 5SC UPS - 500/3000VA - Datasheet

# Compliance information

EU DoC Eaton 5SC

#### User guides

Eaton 5SC Rack-RT UPS - 1000i Rack2U/1500i Rack2U/2200i

RT2U/3000i RT2U - Installation and user manual



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia