Eaton 9PX1500RT

Catalog Number: 9PX1500RT

Eaton 9PX UPS, 2U, 1500 VA, 1350 W, 5-15P input, Outputs: (8) 5-15R, 120V

General specifications

Product Name Eaton 9PX UPS

UPC 743172081261

Product Height 3.4 in

Product Weight 42.5 lb

Compliances

IEC 62040-2 Cat C1 CISPR22 Class B FCC part 15 Class B VCCI Class B Catalog Number 9PX1500RT

Product Length/Depth 17.7 in

Product Width 17.3 in

Warranty 3 year limited

Certifications cULus Listed NOM





Product specifications

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Output waveform

True sine wave

VA rating 1500 VA

Max number of battery packs

4

Wattage

1350 W

Output power factor

0.9

Form factor Rack/tower

Receptacle

(8) 5-15R

Standard factory warranty

3-YEAR FACTORY WARRANTY

- 3 years
- Parts, electronics and batteries coverage
- Standard ground shipping
- Technical support

Package contents

9PX1500RT UPS 4-post rail kit Safety manual User manual Tower pedestals RS-232 serial cable USB cable Intelligent Power Software Suite CD

Input connection

5-15P 4

Noise level <40 dB at 1 meter

Runtime graph

View runtime graph

Resources

Brochures

Eaton 9PX 700-3000 VA UPS brochure Eaton UPS and battery services Eaton UPS Services Quick Guide 2021

Drawings

Eaton 9PX UPS 700-1500 VA technical drawing Eaton 9PX UPS 700-1500 VA 120V outline drawing Battery Integration System Pro-E drawing

Specifications and datasheets

9PX 700-3000 VA UPS technical specification Eaton 9PX UPS guide specification: 700-3000 VA Eaton Specification Sheet - 9PX1500RT

User guides 9PX battery integration system user guide 9PX 700-3000 VA 2U UPS user guide 9PX 2-post rack kit user guide

Software compatibility

Intelligent Power Software Suite

User interface

Graphical display, 5-button programmable menu

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Battery type

Sealed, lead-acid

Efficiency

90%

Rack size

2U

Number of Outputs 5-15R

8

Voltage

120V

Input cord length

8 ft

Temperature range 0° to 40°C (32° to 104°F)

Communication

MiniSlot + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relayCommunication slot

Relative humidity

0-96% non-condensing

Extended service plans

ADVANCED DEPOT EXCHANGE

- 5-year depot repair: 9SW5Y-1500UC
- Expedited parts coverage for 5 years
- Parts, electronics and UPS batteries coverage
- Next business day shipping
- Technical support

5-YEAR ON-SITE PLAN: WFLN75XX-2509UC

- On-site parts and labor coverage for years 5
- Parts, electronics and UPS batteries coverage
- 24x7 on-site labor coverage, next-day response
- Next-day shipping

- Technical support

Color

Black/silver

Rack mounting kit

Yes

Extended battery capability

Add up to 4 extended battery modules (EBM). Part number 9PXEBM48RT

Output voltage range

±1% steady-state

Topology Online/Double-conversion

BTU Rating Online: 512, Battery: 897

Output frequency

50/60 Hz

Runtime at full load

5 min

Type UPS

Output nominal voltage 120V default (100/110/120/125V)

Input nominal voltage 120V default (100/110/120/125V)

Input power factor

>0.99 typical

Expansion slots

(1) Mini-Slot (MS) expansion port. The following optional connectivity cards may be ordered separately.
Gigabit Network Card part number: NETWORK-M2
Modbus card part number: INDGW-M2
Relay card part number: RELAY-MS

Input frequency range 60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Internal bypass

Yes

Altitude

0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia