# Yuasa Technical Data Sheet

### Yuasa NP17-12I Industrial VRLA Battery

Tuasa NF 17-121 muustilai VKLA Battery	
<b>Specifications</b> Nominal voltage (V) 10-hr rate Capacity to 10.8V at 20°C (Ah)	12 15.7
<b>Dimensions</b> Length (mm) Width (mm) Height (mm) Mass (kg)	181 (±1) 76 (±1) 167 (±2) 6.1
<b>Terminal Type</b> Threaded terminal - (M=Male or F=Female) Torque (Nm)	M5 (F) 2.45
<b>Operating Temperature Range</b> Storage (in fully charged condition) Charge Discharge	-20°C to +60°C -15°C to +50°C -20°C to +60°C
<b>Storage</b> Capacity loss per month at 20°C (% approx.)	3
<b>Case Material</b> Standard FR version available	ABS (UL94:HB) UL94:V0
<b>Charge Voltage</b> Float charge voltage at 20°C (V)/Block Float charge voltage at 20°C (V)/Cell Float Chg voltage tmp correction factor from std 20°C (mV)	13.65 (±1%) 2.275 (±1%) -3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block Cyclic (or Boost) charge Voltage at 20°C (V)/Cell Cyclic Chg voltage tmp correction factor from std 20°C (mV)	2.42 (±3%)
<b>Charge Current</b> Float charge current limit (A) Cyclic (or Boost) charge current limit (A)	No limit 4.25
<b>Maximum Discharge Current</b> 1 second (A) 1 minute (A)	500 150
Short-Circuit Current & Internal Resistance Internal resistance - according to EN IEC 60896-2 ( $m\Omega$ )	1 34.47
Short-Circuit current - according to EN IEC 60896-21 (A)	421
<b>Impedance</b> Measured at 1 kHz (mΩ)	15
<b>Design Life &amp; Approvals</b> EUROBAT Classification: Standard Commercial	3 to 5 years





Layout



## 3rd Party Certifications

ISO9001 - Quality Management Systems



# Safety

#### Installation

Can be installed and operated in any orientation except permanently inverted.

## Handles

Batteries must not be suspended by their handles (where fitted).

#### Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

### Gas release

up to 5

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

#### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.



YUASA

The world's leading battery manufacturer

Yuasa design life at 20°C (yrs)

www.yuasaeurope.com