# Yuasa Technical Data Sheet

## Yuasa NPL200-6 Industrial VRLA Battery

**Specifications** 

Nominal voltage (V) 6 10-hr rate Capacity to 1.8V/Cell at 20°C (Ah) 176

**Dimensions** 

 Length (mm)
  $398 (\pm 0.7)$  

 Width (mm)
  $176 (\pm 0.5)$  

 Height (mm)
  $250 (\pm 0.7)$  

 Mass (kg)
 39 

**Terminal Type** 

Threaded terminal - (M=Male or F=Female) M10 LUG Torque (Nm) 16.5

**Operating Temperature Range** 

Storage (in fully charged condition)  $-20^{\circ}\text{C to } +50^{\circ}\text{C}$ Charge  $-15^{\circ}\text{C to } +50^{\circ}\text{C}$ Discharge  $-20^{\circ}\text{C to } +60^{\circ}\text{C}$ 

**Storage** 

Capacity loss per month at 20°C (% approx.)

**Case Material** 

Standard ABS (UL94:HB) FR version available UL94:V0

**Charge Voltage** 

Float charge voltage at 20°C (V)/Block 6.825 ( $\pm$ 1%) Float charge voltage at 20°C (V)/Cell 2.275 ( $\pm$ 1%)

Float Chg voltage tmp correction factor from std -3

20°C (mV)

Cyclic (or Boost) charge Voltage at 20°C (V)/Block 7.26 ( $\pm$ 3%) Cyclic (or Boost) charge Voltage at 20°C (V)/Cell 2.42 ( $\pm$ 3%) Cyclic Chg voltage tmp correction factor from std -4

20°C (mV)

**Charge Current** 

Float charge current limit (A) No limit Cyclic (or Boost) charge current limit (A) 50

**Maximum Discharge Current** 

1 second (A) 1500 1 minute (A) 600

**Impedance** 

Measured at 1 kHz (m $\Omega$ ) 1.3


**Design Life & Approvals** 

EUROBAT Classification: Long life 10 to 12 years Yuasa design life at 20°C (yrs) up to 10 years





## Layout



## **3rd Party Certifications**

ISO9001 - Quality Management Systems UNDERWRITERS LABORATORIES Inc.





# Safety

## Installation

Can be installed and operated in any orientation except permanently inverted.

#### Handles

Batteries must not be suspended by their handles (where fitted).

#### **Vent valves**

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

# Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

#### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.







