

Eaton 3S Gen2(3S700B)
Eaton 3S Gen2 - UPS - BS,(4) UK,(4) UK surge only,USB charge (2),tower - AC 220/230/240 V - 420 Watt - 700 VA - 1-phase - 7 Ah - USB - output connectors:8 - United Kingdom - black / white



Eaton 3S provides power and surge protection for desktop computers,wireless networks,gaming consoles,and other critical electronics in your home or business. Attractive design and glossy finish make the 3S a perfect fit for the modern office environment. Compact unit fits on or under your desk or can be mounted on a wall. Easy-to-replace battery helps to extend UPS service life. HID-compliant USB port (cable supplied),for automatic integration with major operating systems (Windows/Mac OS/Linux).

Main Specifications

Product Description	Eaton 3S Gen2 - UPS - BS,(4) UK,(4) UK surge only,USB charge (2),tower - 420 Watt - 700 VA
Device Type	UPS - external
Weight	4 kg
Localisation	United Kingdom
Input Wiring	1-phase
Input Voltage	AC 220/230/240 V
Output Voltage	AC 220/230/240 V
Power Capacity	420 Watt / 700 VA
Output connectors	4 x power BS (surge) 4 x power BS (UPS and surge) 2 x 4 pin USB Type A 2 A
Battery	Lead Acid - 7 Ah
Batteries Qty	1
Networking	USB
Colour	Black / white
Dimensions (WxDxH)	17 cm x 33.5 cm x 8.6 cm
Manufacturer Warranty	2-year warranty

Extended Specification

General

Device Type	UPS - external
Colour	Black / white
Localisation	United Kingdom

Power Device

UPS Technology	Off-line
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 184 - 264 V
Input Voltage Range (Adjustable)	AC 161 - 284 V
Input Wiring	1-phase
Frequency Required	50 - 60 Hz

Power Output Connectors Details	4 x power BS (surge)
	4 x power BS (UPS and surge)
	2 x 4 pin USB Type A 2 A
Output Voltage	AC 220/230/240 V
Power Capacity	420 Watt / 700 VA
Surge Suppression	Yes
Efficiency	98%
Power Factor (PF)	0.6

Battery

Quantity	1
Technology	Lead Acid
Capacity	7 Ah
Features	Sealed

Networking

Remote Management Interface	USB
-----------------------------	-----

Expansion / Connectivity

Interfaces	1 x USB - 4 pin USB Type B
------------	----------------------------

Miscellaneous

Cables Included	Power cable 1.5 m USB cable - external
Features	Replaceable battery,HID compatible,deep discharge protection,cold-start function,automatic shut down,automatic battery test
Compliant Standards	EAC,IEC/EN 62040-1,IEC/EN 62040-2

Manufacturer Warranty

Service &Support	Limited warranty - 2 years
------------------	----------------------------

Environmental Parameters

Humidity Range Operating	0 - 85% RH (non-condensing)
Sound Emission	25 dB

Dimensions &Weight

Width	17 cm
Depth	33.5 cm
Height	8.6 cm
Weight	4 kg

Product data is provided by CNET,we do not warrant the accuracy and completeness of the material contained in this data sheet