

## Eaton 3S Gen2(3S850B)

Eaton 3S Gen2 - UPS - BS, (4) UK, (4) UK surge only, USB charge (2), tower - AC 220/230/240 V - 510 Watt - 850 VA - 1-phase - 9 Ah - USB - output connectors:8 - United Kingdom - black / white



Eaton 3S provides power and surge protection for desktop computers, wireless networks, gaming consoles, and other critical electronics in your home or business. Attractive design and glossy finish make the 3S a perfect fit for the modern office environment. Compact unit fits on or under your desk or can be mounted on a wall. Easy-to-replace battery helps to extend UPS service life. HID-compliant USB port (cable supplied), for automatic integration with major operating systems (Windows/Mac OS/Linux).

### Main Specifications

Product Description	Eaton 3S Gen2 - UPS - BS, (4) UK, (4) UK surge only, USB charge (2), tower - 510 Watt - 850 VA
Device Type	UPS - external
Weight	4.3 kg
Localisation	United Kingdom
Input Wiring	1-phase
Input Voltage	AC 220/230/240 V
Output Voltage	AC 220/230/240 V
Power Capacity	510 Watt / 850 VA
Output connectors	4 x power BS (surge)   4 x power BS (UPS and surge)   2 x 4 pin USB Type A 2 A
Battery	Lead Acid - 9 Ah
Batteries Qty	1
Networking	USB
Colour	Black / white
Dimensions (WxDxH)	33.5 cm x 17 cm x 8.6 cm
Manufacturer Warranty	2-year warranty

### Extended Specification

#### General

Device Type	UPS - external
Colour	Black / white
Localisation	United Kingdom

#### Power Device

UPS Technology	Off-line
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 184 - 264 V
Input Voltage Range (Adjustable)	AC 161 - 284 V
Input Wiring	1-phase
Frequency Required	50 - 60 Hz

Power Output Connectors Details	4 x power BS (surge) 4 x power BS (UPS and surge) 2 x 4 pin USB Type A 2 A
---------------------------------	--

Output Voltage	AC 220/230/240 V
----------------	------------------

Power Capacity	510 Watt / 850 VA
----------------	-------------------

Surge Suppression	Yes
-------------------	-----

Efficiency	98%
------------	-----

Power Factor (PF)	0.6
-------------------	-----

### Battery

Quantity	1
----------	---

Technology	Lead Acid
------------	-----------

Capacity	9 Ah
----------	------

Features	Sealed
----------	--------

### Networking

Remote Management Interface	USB
-----------------------------	-----

### Expansion / Connectivity

Interfaces	1 x USB - 4 pin USB Type B
------------	----------------------------

### Miscellaneous

Cables Included	Power cable 1.5 m USB cable - external
-----------------	---

Features	Replaceable battery,HID compatible,deep discharge protection,cold-start function,automatic shut down,automatic battery test
----------	---

Compliant Standards	EAC,IEC/EN 62040-1,IEC/EN 62040-2
---------------------	-----------------------------------

### Manufacturer Warranty

Service &Support	Limited warranty - 2 years
------------------	----------------------------

### Environmental Parameters

Humidity Range Operating	0 - 85% RH (non-condensing)
--------------------------	-----------------------------

Sound Emission	25 dB
----------------	-------

### Dimensions &Weight

Width	33.5 cm
-------	---------

Depth	17 cm
-------	-------

Height	8.6 cm
--------	--------

Weight	4.3 kg
--------	--------