

Specifications

Eaton 5P650IRNG2BS



Eaton 5P Gen2 UPS, 650 VA, 520 W, Input: C14, Outputs: (4) C13, Rack, 1U, Network card, BS Input cord



General specifications

PRODUCT NAME	Eaton 5P Gen2 UPS
CATALOG NUMBER	5P650IRNG2BS
EAN	3553340710476
PRODUCT LENGTH/DEPTH	361 mm
PRODUCT HEIGHT	43.2 mm
PRODUCT WIDTH	438 mm
PRODUCT WEIGHT	8.943 kg
WARRANTY	3 year on electronics, 2 year on battery
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive WEEE Directive Packaging Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778 CSA-C22.2 CE UKCA Cm Ukr KCC cTUVus BIS

Additional information

AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black/silver
CONSTRUCTION TYPE	482.6 mm (19 inch) device
EFFICIENCY AT MAX. LOAD	97
ENCLOSURE	Black/silver
PACKAGE CONTENTS	• Rack-mounting kit • Cable locking system • USB cable • (2) IEC-IEC cables • Quickstart guide • Safety instructions • Network card • BS Input cord
PHASE (INPUT)	1
PHASE (OUTPUT)	1
RACK MOUNTING KIT	Yes
RACK SIZE	1U

Communication

COMMUNICATION	• USB port (HID compliant) • Serial port (RS232) • Mini-terminal block for remote On/Off and Remote Power Off • Dry contacts (2 outputs, optocoupler, RJ)
ETHERNET INTERFACE	Yes
EXPANSION SLOTS	One slot, network card included
POTENTIAL FREE SWITCH CONTACT	Yes
SOFTWARE COMPATIBILITY	Eaton Brightlayer Software suite
TYPE OF INTERFACE	LCD Display with blue backlight

Battery specifications

BATTERY MANAGEMENT	ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection
BATTERY QUANTITY	2
BATTERY RATING	6 V / 9 Ah
BATTERY REPLACEMENT	User replaceable
BATTERY TYPE	Lead-acid maintenance-free (replaceable)
EXTENDED BATTERY CAPABILITY	No
RUNTIME GRAPH	\$row.attributeValue.cdata

Electrical input

INPUT CONNECTION	C14
INPUT FREQUENCY RANGE	47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode
INPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
INPUT VOLTAGE RANGE	160-294 V (adjustable to 150 V-294 V)
NOMINAL FREQUENCY	50-60 Hz

Electrical output

OUTPUT FREQUENCY	50/60 Hz
OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
OUTPUT VOLTAGE RANGE	230 V (+6%/-10%)
RECEPTACLE	(4) C13
TOPOLOGY	Line-interactive
VOLTAGE	230V
WATTAGE	520

Resources

BROCHURES	Eaton 5P Gen2 UPS datasheet
DECLARATIONS OF CONFORMITY	EU Declaration of conformity Eaton 5P Gen2 UPS
MANUALS AND USER GUIDES	Eaton 5P Gen2 Rack - Advanced user guide Eaton 5P Gen2 Quick Start Guide

Environmental

ALTITUDE	3000 m
NOISE LEVEL	<35 dB at 1 meter
RELATIVE HUMIDITY	0-90% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
BTU RATING	Online: 53, Battery: 461 BTU/hr

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

