

# 12V

# 1500A

# GB50



## START DEAD BATTERIES. ULTRASAFE® LITHIUM JUMP STARTER.™

### GAS & DIESEL

#### UP TO 7.0L GAS & 4.5L DIESEL.

Designed for gas engines up to 7 liters and diesel engines up to 4.5 liters for small diesel cars, SUVs, boats, trucks, ATVs, motorcycles and more.

### USB

#### CHARGE & RECHARGE.

It's internal battery can be used to recharge any personal mobile devices like smartphones, tablets, or any other USB device, and can be recharged by any powered USB port.

### 30X

#### UP TO 30 JUMPSTARTS.

Compact, yet powerful lithium jump starter rated at 1,500 amps. Full power to jump start a vehicle up to 30 times on a single charge.

### ULTRA SAFE

#### SPARK PROOF TECHNOLOGY.

Safely connect to any 12-volt car battery with our mistake-proof design featuring spark-proof technology and reverse polarity protection.



**NOCO**

30339 Diamond Parkway, #102  
Glenwillow, OH 44139 | USA  
1.800.456.6626

no.co

LEAD ACID

WET

GEL

MF

EFB

AGM

AUTO | MARINE | RV | POWERSPORT | LAWN & GARDEN



## INTERFACE

### POWER LED

The jump starter is in standby or the battery voltage is too low for the jump starter to detect.



### POWER BUTTON

Push to turn unit "On" & "Off".



### CHARGE LED

Indicates the charge level of the internal battery.



### BOOST LED

Illuminates white when boost is active. The LED flashes white when manual override feature is active.



### HOT/COLD INDICATOR

Illuminates solid or flashes red when internal temperature is too high. Illuminates solid or flashes blue when internal temperature is too low.



### LIGHT MODE BUTTON

Toggles the ultra-bright LED light through 7 light modes: 100% > 50% > 10% > SOS > Blink > Strobe > Off



### ERROR

Illuminates Red if reverse polarity is detected. Blinks "on" and "off" in various sequences to convey error conditions.




### MANUAL OVERRIDE.


Press and hold the manual override button for 3 seconds, until the Boost LED starts flashing, to enter into manual mode.



## WHAT'S IN THE BOX



\*Accessories not to scale with GB50



## CHARGE DEVICES.

Recharge your personal devices on the go, like smartphones, tablets, e-watches and more - up to 6 smartphone recharges.

## RECHARGE TIME

0.5A	12hr
1A	6hr
2A	3hr

## TECHNICAL SPECIFICATIONS

INTERNAL BATTERY:	35 Watt-Hour Lithium Ion	
PEAK CURRENT RATING:	1500A	
OPERATING TEMPERATURE:	-4°F to +122°F (-20°C to +50°C)	
CHARGING TEMPERATURE:	32°F to +104°F (0°C to +40°C)	
MICRO USB (INPUT):	5V, 2.1A	
USB (OUTPUT):	5V, 2.1A	
HOUSING PROTECTION:	IP65 (w/Ports Closed)	
COOLING:	Natural Convection	
UNIT WEIGHT:	1.65 lbs (0.74kg)	
UNIT WEIGHT W/ CLAMPS & ACCESSORIES:	2.71 lbs (1.22kg)	
LED FLASHLIGHT:	200 Lumens	
VOLUMETRICS:	<b>Retail Packaging:</b>	<b>Master Carton:</b>
	Dimensions: 3.9"x4.7"x9.1" Weight: 3.35lbs UPC: 0-46221-18017-6	Dimensions: 10.25"x13.5"x11.375" Weight: 22.1lbs Quantity: 6 UCC: 10046221180173
	<b>Inner Carton:</b>	<b>Units Per Pallet:</b>
	Dimensions: 4.1"x9.37"x5.27" Weight: 3.51lbs	NA - 360 Units EU - 234 Units

**NOCO**

30339 Diamond Parkway, #102  
Glenwillow, OH 44139 | USA  
1.800.456.6626

**no.co**

XGC  
Extension Cable

