

SPECIFICATIONS

Nominal Voltage (V) 12V

Nominal Capacity

20 hour rate (6.25A to 10.50V)	125Ah
10 hour rate (11.875A to 10.50V)	118.75Ah
8 hour rate (14.625A to 10.50V)	117Ah
5 hour rate (21.25A to 10.20V)	106.3Ah
1 hour rate (75A to 9.60V)	75Ah
1C (125A to 9.60V)	62.5Ah

Weight Approx. 39kg (85.8Lbs.)

Internal Resistance (at 1KHz) Approx. 7.0 mΩ

Maximum Discharge Current

5 seconds: 750A

Charging Parameters at 25°C (77°F)

Maximum Charging Current	37.5A
Boost Charging Voltage	14.4 to 15.0V
Boost Charge Time	8-9Hr
Float Charging Voltage	13.5 to 13.8V

Operating Temperature Range

Charge	-15°C (5°F) to 40°C (104°F)
Discharge	-15°C (5°F) to 50°C (122°F)
Storage	-15°C (5°F) to 40°C (104°F)

Charge Retention at 20°C (68°F)

1 month	98%
3 months	96%
6 months	94%

Case Material ABS UL94 HB


Design Life EUROBAT (20°C) >12 YEARS VERY LONG LIFE

Sealed Valve-Regulated Lead-Acid Battery



DIMENSIONS

mm(inch)



Terminal





F18

Recommended torque value

M8: 12 N-m (122 kgf-cm)

Maximum allowable torque value

M8: 20 N-m (204 kgf-cm)



MK Battery EMEA GmbH

Kleinsteinbacher Strasse 44
76228, Karlsruhe-Stupferich Germany
Tel: +49 (0) 69 9073 2250 • Email: salescentraleurope@mkbattery.com

