

# Product datasheet

Specifications



## APC Smart-UPS On-Line, 2200VA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

SRT2200XLI

### Overview

<b>Presentation</b>	High density, double-conversion on-line power protection with scalable runtime.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	1980 W
<b>Rated power in VA</b>	2200 VA
<b>Input Connection Type</b>	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
<b>Output connection type</b>	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19
<b>Cable length</b>	2.44 m
<b>Number of cables</b>	1
<b>Battery type</b>	Lead-acid battery
<b>Provided equipment</b>	CD with software Country-specific detachable power cord Documentation CD Installation guide Removable support feet USB cable Warranty card

### General

<b>Product web sub-family</b>	High density
<b>Number of power module</b>	1400
<b>Number of power module free slots</b>	0
<b>Number of power module filled slots</b>	0
<b>Redundant</b>	No

## Physical

Colour	Black
Height	43.2 cm
Width	8.5 cm
Depth	58.4 cm
Net weight	25 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

## Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	100...275 V adjustable (half load)

## Output

Maximum configurable power in W	1980 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	2200 VA

## Conformance


Product certifications	CE EAC RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m

Acoustic level	55 dBA
Heat dissipation	703 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery voltage	72 V
Battery charger power	122 W rated
Battery power in VAh	367 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC141</a> 
Battery option	SRT72BP 1 1101 VAh SRT72BP 2 1835 VAh SRT72BP 3 2569 VAh SRT72BP 4 3303 VAh SRT72BP 5 4037 VAh SRT72BP 6 4771 VAh SRT72BP 8 6239 VAh SRT72BP 10 7707 VAh
Extended runtime	1

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	81 cm
Package 1 Length	59.9 cm
Package 1 Weight	30.84 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

## Contractual warranty

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

## Recommended replacement(s)