



Dryfit technology



SONNENSCHN BATTERIES



Overview

The batteries in the Sonnenschein dryfit range are compact, versatile and can be used in a wide variety of applications. Dryfit technology consists of closed-system batteries in which the electrolyte is fixed in a gel. This means that no maintenance whatsoever is required throughout the entire service life of the battery. The special advantage of the Sonnenschein dryfit battery lies in the batteries' suitability for extreme operating conditions and the highest demands on reliability.

Range



- Absolutely maintenance-free
- Non-hazardous
- Robust, safe and reliable
- Low self discharge
- Extremely low gassing
- Clean and environmentally friendly

Part No	Volt	AH	L	W	H	Weight
SONNENSCHN GF Y 12 VOLT RANGE						
GF12014YF	12	15.0	181	76	167	6.0
GF12022YF	12	24.0	166	175	125	9.6
GF12025YG	12	28.0	197	132	180	11.1
GF12033YG1	12	38.0	210	175	175	14.6
GF12033YG2	12	38.0	210	175	175	14.6
GF12040Y	12	48.0	242	175	190	16.0
GF12044Y	12	50.0	261	135	230	19.0
GF12051Y1	12	56.0	278	175	190	20.8
GF12051YG1	12	56.0	278	175	190	20.8
GF12051Y2	12	56.0	278	175	190	20.8
GF12052YO	12	60.0	261	170	178	19.8
GF12063YO	12	70.0	261	171	210	23.0
GF12065Y	12	78.0	353	175	190	26.8
GF12072Y	12	80.0	330	171	235.5	30.0
GF12094Y	12	110.0	284	267	230	40.0

Part No	Volt	AH	L	W	H	Weight
SONNENSCHN GF V 12 VOLT RANGE						
GF12050V	12	55.0	278	175	190	19.0
GF12070V	12	79.0	330	171	235.5	26.5
GF12076V	12	87.9	330	171	235.5	28.8
GF12090V	12	96.0	513	189	219	39.0
GF12105V	12	120.0	345	174	283	38.7
GF12110V	12	116.0	513	223	219	45.5
GF12160V	12	196.0	518	274	238	62.5
SONNENSCHN GF V 6 VOLT RANGE						
GF06160V1	6	196.0	246	192	275	29.0
GF06160V2	6	196.0	264	183	270	33.0
GF06180V	6	200.0	246	192	275	31.0
GF06180VQ	6	200.0	246	192	282	31.5
GF06240V	6	270.0	311	181.1	358	48.0